

STAGEMAKER®

new
250 kg / 1 fall



Different models to suit any application						60 Hz		50 Hz	Hoist Configuration							
Cap. (Ton)	Cap. (kg)	Frame (Model)	Fall	Chain Size (MM)	Motor Power (HP)	Speed (fpm)	Speed (m/min)	Speed (m/min)	A	B	C	D	E	S	V	
1/16	60	SM1	1	3.1X9.3	0.33	32	9.6	8	•	•	•					
1/16	60	SM1	1	3.1X9.3	0.33	64	19.2	16	•	•	•					
1/8	125	SM1	1	3.1X9.3	0.16	16	4.8	4						•		
1/8	125	SM1	1	3.1X9.3	0.33	32	9.6	8	•	•	•					
1/4	250	SM2	1	4x12	0.33	16	4.8	4	•	•	•					
1/4	250	SM5	1	4.8X12.5	0.65	16	4.8	4	•	•	•			•		
1/4	250	SM5	1	4.8X12.5	1.3	32	9.6	8	•	•	•					
1/4	250	SM5	1	4.8X12.5	1.3	64	19.2	16	•	•	•					
1/4	250	SM10	1	6.8X17.8	2.8	64	19.2	16				•				
1/2	500	SM5	1	4.8X12.5	0.65	16	4.8	4	•	•	•			•		
1/2	500	SM5	1	4.8X12.5	1.3	32	9.6	8	•	•	•					
1/2	500	SM10	1	6.8X17.8	1.4	16	4.8	4				•				
1/2	500	SM10	1	6.8X17.8	2.8	32	9.6	8				•				
1/2	500	SM10	1	6.8X17.8	2.8	64	19.2	16	•	•	•			•		
1/2	500	SM10	1	6.8X17.8	2.8	4-64	1.2-19.2	1-16							•	
1	1000	SM10	1	6.8X17.8	1.4	16	4.8	4	•	•	•			•		
1	1000	SM10	1	6.8X17.8	2.8	32	9.6	8	•	•	•			•		
1	1000	SM10	2	6.8X17.8	1.4	8	2.4	2				•				
1	1000	SM10	2	6.8X17.8	2.8	16	4.8	4				•				
1	1000	SM10	1	6.8X17.8	2.8	2-32	0.6-9.6	0.5-8							•	
1.5	1600	SM16	1	9.0X27.0	5.6	32/8	9.6/2.4	8/2		†						
2	2000	SM10	2	6.8X17.8	1.4	8	2.4	2	•	•	•			•		
2	2000	SM10	2	6.8X17.8	2.8	16	4.8	4	•	•	•			•		
2	2000	SM10	2	6.8X17.8	2.8	1-16	0.3-4.8	0.25-4							•	
2	2000	SM20	1	9.0X27.0	5.6	32/8	9.6/2.4	8/2		†						
2.5	2500	SM25	1	9.0X27.0	5.6	24/6	7.6/1.8	6.3-1.5		†						
5	5000	SM25	2	9.0X27.0	5.6	12/3	3.8/0.9	3.2-0.75		†						

• Configuration available in Normal position or Normal/Inverted position if specially equipped
 † Configuration available in Normal position only

