

SHEAVE	11
---------------	-----------

- Groove 45°
- Life lubricated bearing
- Groove hardness is 220 HB

hoist	FEM classification	D nominal (mm) hook block	D nominal (mm) frame	Groove radius mm	D rope mm
SM1021	1Am, 2m , 3m	126	-	3.7	5.5
SM1042	1Am, 2m , 3m	126	-	3.7	5.5
SM1041	1Am, 2m , 3m	126	126	3.7	5.5
SM2021	1Am	126	-	3.7	7
SM2021	2m , 3m	156.5	-	3.7	7
SM2041	1Am	156.5	126	3.7	7
SM2041	2m , 3m	156.5	156.5	3.7	7
SM3021	1Am	162	-	4.8	9
SM3021	2m , 3m	231	-	4.8	9
SM3042	1Am, 2m , 3m	156.5	-	3.7	7
SM3041	1Am	162	162	4.8	9
SM3041	2m , 3m	231	231	4.8	9
SM3061	1Am, 2m , 3m	231	231	4.8	9
SM4021	1Am	235	-	7	13
SM4021	2m , 3m	293	-	7	13
SM4042	1Am, 2m , 3m	231	-	4.8	9
SM4041	1Am	235	235	7	13
SM4041	2m , 3m	293	293	7	13
SM4061	1Am, 2m , 3m	293	293	7	13
SM5021	1Am	291	-	8.5	16
SM5021	2m , 3m	360	-	8.5	16
SM5042	1Am, 2m , 3m	293	-	7	13
SM5041	1Am	291	291	8.5	16
SM5041	2m , 3m	360	360	8.5	16
SM5061	1Am, 2m , 3m	360	360	8.5	16
SM5082	1 Am	235	293	7	13
SM5122					
SM5082	2m, 3m	293	293	7	13
SM5122					
SM5162	1 Am	226	226	5.3	10
SM6021	1 Am	371	371	10.6	20
SM6041					
SM6021	2m, 3m	448	448	10.6	20
SM6041					
SM6042	1 Am	291	360	8.5	16
SM6082					
SM6122					
SM6042	2m, 3m	360	360	8.5	16
SM6082					
SM6122					
SM6162	1 Bm	289	358	7.5	14