



® R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502
Phone: (937) 328-5100
Fax: (937) 525-5130
www.rmhoist.com

03/09/10

LEAD TIME MATRIX (subject to change without notice)

CATEGORY 1 → 4 weeks ARO

"Quick Delivery" crane packages from Quotemaster™
Hoists found in the "RX Program"

SX5021 / SX5041 with P5 / F gear and D, E, or F drum with double girder "adjustable load beam" for 5 ft - 7 ft gauge
Same as above but with P6 / H gear (460V or 575V only)

End trucks, bridge drives, bridge panels, radios, pendants found in the "Quick Delivery" offering - NO modifications

CATEGTORY 1.5 → 4 weeks ARO

Standard hoists-only (no options) per the following criteria for 208, 230, 460, or 575-3-60 Hz (unless otherwise noted).
If you need these hoists as part of a crane package, please contact Inside Sales!

FOOTMOUNT:

SX4021 / SX4041 / SX4061 with P3 / F gear and B, C, or D drum

SX4061 with P4 / H gear and B, C, or D drum (460V or 575V only)

SX5021 / SX5041 / SX5061 / SX5081 with P5 / F gear and D, E, F, or G drum
Same as above but with P6 / H gear (460V or 575V only)

SX6061 with P6 / E or F gear and E or F drum (460V or 575V only)

DOUBLE GIRDER:

SX4021 / SX4041 with P3 / F gear, *B drum*, gauge = 1200 / 1219 / 1372 / 1524 / 1676 / 1829 / 2134 / 2591 mm

SX4021 / SX4041 with P3 / F gear, *C drum*, gauge = 1219 / 1372 / 1524 / 1676 / 1700 / 1829 / 2000 / 2134 / 2591 mm

SX4021 / SX4041 with P3 / F gear, *D drum*, gauge = 1524 / 1700 / 1829 / 2000 / 2438 / 2591 mm

SX4061 with P3 / F gear, *C drum*, gauge = 1400 / 1524 / 1700 / 2000 / 2134 mm
Same as above but P4 / H gear (460V or 575V only)

SX4061 with P3 / F gear, *D drum*, gauge = 1524 / 1700 / 2000 / 2134 mm
Same as above but P4 / H gear (460V or 575V only)

NOTE: 1" = 25.4 mm
Divide mm by 25.4 to get inches.



® R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502
Phone: (937) 328-5100
Fax: (937) 525-5130
www.rmhoist.com

03/09/10

CATEGORY 1.5 → 4 weeks ARO (continued)

SX5021 / SX5041 with P5 / F gear, *D drum*, gauge = 1372 / 1524 / 1676 / 1700 / 1828 / 2000 / 2134 / 2286 / 2438 / 2743 / 3048 mm
Same as above but P6 / H gear (460V or 575V only)

SX5021 / SX5041 with P5 / F gear, *E drum*, gauge = 1372 / 1524 / 1676 / 1700 / 1828 / 2000 / 2134 / 2286 / 2438 / 2743 / 3048 mm
Same as above but P6 / H gear (460V or 575V only)

SX5021 / SX5041 with P5 / F gear, *F drum*, gauge = 1676 / 1700 / 1981 / 2000 / 2143 / 2286 / 2438 / 2591 / 2743 / 3048 mm
Same as above but P6 / H gear (460V or 575V only)

SX5021 / SX5041 with P5 / F gear, *G drum*, gauge = 1676 / 1981 / 2000 / 2134 / 2286 / 2438 / 2591 / 2743 / 3048 mm
Same as above but P6 / H gear (460V or 575V only)

SX5061 / SX5081 with P5 / F gear, *D drum*, gauge = 1400 / 1524 / 1676 / 1700 / 1829 mm
Same as above but with P6 / H gear (460V or 575V only)

SX5061 / SX5081 with P5 / F gear, *E drum*, gauge = 1524 / 1676 / 1700 / 1829 / 2000 / 2438 mm
Same as above but with P6 / H gear (460V or 575V only)

SX5061 / SX5081 with P5 / F gear, *F drum*, gauge = 2134 / 2286 / 2400 / 2438 / 2743 / 3048 mm
Same as above but with P6 / H gear (460V or 575V only)

SX5061 / SX5081 with P5 / F gear, *G drum*, gauge = 2286 / 2400 / 2438 / 2743 / 3048 mm
Same as above but with P6 / H gear (460V or 575V only)

SX6061 with P6 / E or F gear, *E drum*, gauge = 1700 / 1829 / 1981 / 2134 / 2286 / 2400 / 2438 / 2743 / 3048 / 3100 mm (460V or 575V only)

SX6061 with P6 / E or F gear, *F drum*, gauge = 1981 / 2134 / 2286 / 2400 / 2438 / 2743 / 3048 / 3100 / 3400 / 3800 mm (460V or 575V only)

Additional gauges may be available upon request.

End trucks, bridge drives, bridge panels, festoons, radios, and pendants found in the "Quick Delivery" offering

**NOTE: 1" = 25.4 mm
Divide mm by 25.4 to get inches.**



® R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502
Phone: (937) 328-5100
Fax: (937) 525-5130
www.rmhoist.com

03/09/10

CATEGORY 2 → 8 weeks ARO

“Standard Delivery” crane packages from Quotemaster™ and/or hoists/components per the following:
SX1 - SX5 *single reeved* catalogued hoists with F rope drum or shorter
Top running end trucks - RTN32 and smaller
Standard options - including inverter controls IF configured by Quotemaster™.
NO mechanical or electrical design required

CATEGORY 3 → 8 weeks ARO

“Standard Delivery” crane packages from Quotemaster™ and/or hoists/components per the following:
SX1 - SX5 *double reeved* catalogued hoists
SX1 - SX5 *single reeved* low headroom / normal headroom catalogued hoists with G rope drum or longer
SX6081 with P6 / E gear and E or F drum (460V or 575V only)
Smaller-than-standard gauges
Longer-than-standard gauges
Top running end trucks - RTN32 and smaller
Swivel trolleys
Mechanical or electrical design required (ex: Main/aux on common trolley)

CATEGORY 4 → 11 weeks ARO

“Standard Delivery” crane packages from Quotemaster™ and/or hoists/components per the following:
SX6 *single reeved* and SX7 catalogued hoists with F rope drum or shorter
Smaller-than-standard gauges
Longer-than-standard gauges
Top running end trucks – RT50 and smaller
Under running end trucks – all RH models
Standard options - including inverter controls IF configured by Quotemaster™.
NO mechanical or electrical design required

CATEGORY 5 → 17 weeks ARO

“Standard Delivery” crane packages from Quotemaster™ and/or hoists per the following:
SX6 *double reeved* catalogued hoists
SX6 *single reeved* and SX7 catalogued hoists with G rope drum or longer
Mechanical or electrical design required (ex: Main/aux on common trolley)



® R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502
Phone: (937) 328-5100
Fax: (937) 525-5130
www.rmhoist.com

03/09/10

CATEGORY 6 → Add 4 weeks to Cat 3 or Cat 5 lead time above (depending on hoist model)

Catalogued ex-proof *hoists* for Class I, Groups C&D, Div 2
NO options

CATEGORY 7 → 24 weeks ARO

Ex-proof hoists and crane components outside Category 6

CATEGORY 8 → 22 weeks ARO

SHR top running end trucks and associated bridge drives