

Currency: USD
Units: US
Frequency: 60 Hz



March 2, 2009

RX Program

Replacement hoists for emergency breakdown situations.

Equipped with standard hoist features ⁽¹⁾

208, 230, 460, or 575 volts - 3 phase - 60 Hz power supply ⁽²⁾

Refer to page 5 for available options

RX Program lead time and price adders

Normal headroom hoist - 2 business days - USD 636.00 list add per unit

Low headroom hoist - 2 business days - USD 636.00 list add per unit

Double girder hoist - 5 business days - USD 1060.00 list add per unit

(Lead time without adder is 2 - 4 weeks)

Additional discounting beyond your standard R&M discount is not available when the above lead times are applied.

Limited to 2 hoists per order.

Terms and Conditions of Sale

All sales are subject to the R&M Materials Handling, Inc. Standard Terms and Conditions of Sale (Revision 101707), a copy of which is available at www.rmhoist.com or upon request from your R&M Materials Handling, Inc. customer service/sales representatives and the terms of which are incorporated as if fully rewritten herein.

⁽¹⁾ See Spacemaster[®] SX Pricing - Standard Features Section for a list of standard hoist features.

⁽²⁾ See the following RX Program Hoist pages for voltage exceptions.

R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502



www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
 Units: US
 Frequency: 60 Hz



Page 1
 March 2, 2009

Hoist Model	ASME Duty Class	Lift	Lift Spd. (fpm) 60 Hz	Hoist Motor HP	Reeving	Suspension types - RX Hoist			
						Low HR (L0)	Std. HR (N0)	Double Girder (D0)	D.G. Gauge (Inches)

1 Ton Capacity - Single Reeved

SX10210010PX5EB	H4	39'-4"	32 / 5.3	2.4 / 0.4	2 P.S.	Yes	NA	NA	NA
SX20210010P15FA	H4	39'-4"	40 / 6.6	3 / 0.4	2 P.S.	Yes	Yes	No	NA
SX20210010P15FC	H4	62'-4"	40 / 6.6	3 / 0.4	2 P.S.	Yes	Yes	No	NA
SX20210010R15FA	H4	39'-4"	20 / 3.1	1.5 / 0.4	2 P.S.	Yes ⁽³⁾	Yes ⁽³⁾	No	NA
SX20210010R15FC	H4	62'-4"	20 / 3.1	1.5 / 0.4	2 P.S.	Yes ⁽³⁾	Yes ⁽³⁾	No	NA
SX30210010P26FA	H4+	39'-4"	40 / 6.6	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26FC	H4+	62'-4"	40 / 6.6	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26GA	H4+	39'-4"	50 / 7.8	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26GC	H4+	62'-4"	50 / 7.8	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA

1 1/2 Ton Capacity - Single Reeved

SX30210016P25FA	H4	39'-4"	40 / 6.6	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25FC	H4	62'-4"	40 / 6.6	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25GA	H4	39'-4"	50 / 7.8	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25GC	H4	62'-4"	50 / 7.8	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX20410016P16FA	H4+	19'-8"	20 / 3.1	2.4 / 0.33	4 P.S.	Yes	Yes	No	NA
SX20410016P16FC	H4+	31'-2"	20 / 3.1	2.4 / 0.33	4 P.S.	Yes	Yes	No	NA

Refer to Spacemaster® SX Pricing section for prices.

⁽³⁾ 230v or 460v - 60Hz only

⁽⁴⁾ 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
 4501 Gateway Blvd.
 Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
 subject to change without notice.
 Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
 Units: US
 Frequency: 60 Hz



Page 2
 March 2, 2009

Hoist Model	ASME Duty Class	Lift	Lift Spd. (fpm) 60 Hz	Hoist Motor HP	Reeving	Suspension types - RX Hoist			
						Low HR (L0)	Std. HR (N0)	Double Girder (D0)	D.G. Gauge (Inches)

2 Ton Capacity - Single Reeved

SX10410020PX5EB	H4	19'-8"	16 / 2.6	2.4 / 0.4	4 P.S.	Yes	NA	NA	NA
SX10410020PX5EC	H4	29'-6"	16 / 2.6	2.4 / 0.4	4 P.S.	Yes	NA	NA	NA
SX20410020P15FA	H4	19'-8"	20 / 3.1	3 / 0.4	4 P.S.	Yes	Yes	No	NA
SX20410020P15FC	H4	31'-2"	20 / 3.1	3 / 0.4	4 P.S.	Yes	Yes	No	NA
SX40210020P36FB	H4+	39'-4"	40 / 6.6	5.8/0.9	2 P.S.	Yes	Yes	Yes	55.12
SX40210020P36FC	H4+	59'-0"	40 / 6.6	5.8/0.9	2 P.S.	Yes	Yes	Yes	55.12

2 1/2 Ton Capacity - Single Reeved

SX30410025P26FA	H4+	19'-8"	20 / 3.1	4.7/0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26FC	H4+	31'-2"	20 / 3.1	4.7/0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26GA	H4+	19'-8"	25 / 3.9	4.7/0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26GC	H4+	31'-2"	25 / 3.9	4.7/0.7	4 P.S.	Yes	Yes	No	NA
SX40210025P35FB	H4	39'-4"	40 / 6.6	7.2/1.2	2 P.S.	Yes	Yes	Yes	55.12
SX40210025P35FC	H4	59'-0"	40 / 6.6	7.2/1.2	2 P.S.	Yes	Yes	Yes	55.12

3 Ton Capacity - Single Reeved

SX30410032P25FA	H4	19'-8"	20 / 3.1	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25FC	H4	31'-2"	20 / 3.1	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25GA	H4	19'-8"	25 / 3.9	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25GC	H4	31'-2"	25 / 3.9	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA

Refer to Spacemaster® SX Pricing section for prices.

⁽³⁾ 230v or 460v - 60Hz only

⁽⁴⁾ 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
 4501 Gateway Blvd.
 Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
 subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
 Units: US
 Frequency: 60 Hz



Page 3
 March 2, 2009

Hoist Model	ASME Duty Class	Lift	Lift Spd. (fpm) 60 Hz	Hoist Motor HP	Reeving	Suspension types - RX Hoist			
						Low HR (L0)	Std. HR (N0)	Double Girder (D0)	D.G. Gauge (Inches)

5 Ton Capacity - Single Reeved

SX40410050P35FB	H4	19'-8"	20 / 3.1	7.2 / 1.2	4 P.S.	Yes	Yes	Yes	55.12
SX40410050P35FC	H4	29'-6"	20 / 3.1	7.2 / 1.2	4 P.S.	Yes	Yes	Yes	55.12
SX40410050P35FD	H4	39'-4"	20 / 3.1	7.2 / 1.2	4 P.S.	Yes	No	No	NA
SX50210050P55FD	H4	59'-0"	40 / 6.6	14.8 / 2.1	2 P.S.	Yes	Yes	Yes	55.12
SX50210050P55FE	H4	78'-8"	40 / 6.6	14.8 / 2.1	2 P.S.	Yes	No	Yes	55.12
SX50210050P65HD	H4	59'-0"	60 / 9.8	24.1 / 4	2 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50210050P65HE	H4	78'-8"	60 / 9.8	24.1 / 4	2 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12

7 1/2 Ton Capacity - Single Reeved

SX50410080P56FD	H4+	29'-6"	20 / 3.1	12 / 1.9	4 P.S.	Yes	Yes	Yes	55.12
SX50410080P56FE	H4+	39'-4"	20 / 3.1	12 / 1.9	4 P.S.	Yes	No	Yes	55.12
SX50410080P66HD	H4+	29'-6"	30 / 4.9	19 / 3	4 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50410080P66HE	H4+	39'-4"	30 / 4.9	19 / 3	4 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12

10 Ton Capacity - Single Reeved

SX50410100P55FD	H4	29'-6"	20 / 3.1	14.8 / 2.1	4 P.S.	Yes	Yes	Yes	55.12
SX50410100P55FE	H4	39'-4"	20 / 3.1	14.8 / 2.1	4 P.S.	Yes	No	Yes	55.12
SX50410100P65HD	H4	29'-6"	30 / 4.9	24.1 / 4	4 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50410100P65HE	H4	39'-4"	30 / 4.9	24.1 / 4	4 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12

Refer to Spacemaster[®] SX Pricing section for prices.

⁽³⁾ 230v or 460v - 60Hz only

⁽⁴⁾ 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
 4501 Gateway Blvd.
 Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
 subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
 Units: US
 Frequency: 60 Hz



Page 4
 March 2, 2009

						Suspension types - RX Hoist			
Hoist Model	ASME Duty Class	Lift	Lift Spd. (fpm) 60 Hz	Hoist Motor HP	Reeving	Low HR (L0)	Std. HR (N0)	Double Girder (D0)	D.G. Gauge (Inches)
15 Ton Capacity - Single Reeved									
SX50610150P55FF	H4	32'-9"	13 / 2	14.8 / 2.1	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50610150P65HF	H4	32'-9"	20 / 3.1	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50810160P55FF	H4	26'-2"	10 / 1.5	14.8 / 2.1	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50810160P65HF	H4	26'-2"	16 / 2.4	24.1 / 4	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
20 Ton Capacity - Single Reeved									
SX50810200P54FF	H3	26'-2"	10 / 1.5	14.8 / 2.1	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50810200P64HF	H3	26'-2"	16 / 2.4	24.1 / 4	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610200P66EE	H4+	29'-6"	10 / 1.5	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610200P66FE	H4+	29'-6"	13 / 2	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610200P66EF	H4+	39'-4"	10 / 1.5	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610200P66FF	H4+	39'-4"	13 / 2	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
25 Ton Capacity - Single Reeved									
SX60610250P65EE	H4	29'-6"	10 / 1.5	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610250P65FE	H4	29'-6"	13 / 2	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610250P65EF	H4	39'-4"	10 / 1.5	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610250P65FF	H4	39'-4"	13 / 2	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74

Refer to Spacemaster[®] SX Pricing section for prices.

⁽³⁾ 230v or 460v - 60Hz only

⁽⁴⁾ 460v or 575v - 60Hz only

⁽⁵⁾ 66.93" D.G. gauge - 4 week lead time only



R&M Materials Handling, Inc.
 4501 Gateway Blvd.
 Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
 subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



Page 5
March 2, 2009

Hoist Options - RX Program

Control Transformer and Mainline Contactor (EL05)

Standard on Spacemaster® SX1.
Optional on Spacemaster® SX2 - SX6 Low and Normal headroom hoists only.

Pushbutton Pendant

PBR pendant (E-stop, hoist and trolley motions) is standard on Spacemaster® SX1.
Optional on Spacemaster® SX2 - SX6.

Patented Track Trolley Wheel (TR26)

Add 3 business days to RX lead time.
Normal headroom hoist only.

Hook operated limit switch (manual reset) (HS22)

Standard on Spacemaster® SX1.
Optional on Spacemaster® SX2 - SX6. (This limit switch is in addition to the rotary limit switch.)
Add 3 business days to RX lead time on Low and Normal headroom hoists.
Addition of this limit switch increases headroom about 3 1/2" - 11" from standard depending on the hoist model. If headroom is critical, consult R&M for the actual headroom dimension.

HoistMonitor® (HS11), HoistMonitor® Select (HS12), HoistMonitor® Plus (PE10)

Not available on Spacemaster® SX1
Optional on Spacemaster® SX2 - SX4 and SX5 with P5 motor
Optional on Spacemaster® SX6 with P6 and SX6 that do not include a control transformer and mainline contactor (EL05).
HoistMonitor® will be located in hoist electrical panel.

Refer to Spacemaster® SX Pricing section for prices.



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.
Phone: 937-328-5100 Fax: 937-325-5319