

Currency: USD
Units: US
Frequency: 60 Hz



RX PROGRAM

January 2, 2012

RX Program

Replacement hoists for emergency breakdown situations.

Equipped with standard hoist features (Note 1)
208, 230, 460, or 575 volts - 3 phase - 60 Hz power supply (Note 2)
Refer to page 5 for available options

<u>RX Program Hoist</u>	<u>Lead Time</u>	<u>List Price Adder (per unit)</u>
Normal headroom hoist	2 business days	USD 660.00
Low headroom hoist	2 business days	USD 660.00
Double girder hoist	5 business days	USD 1100.00

(Targeted lead time without adder is 2 - 4 weeks.
For the most current lead times, check the Lead Time Matrix at www.rmhoist.com.)

Additional discounting beyond your standard R&M discount is not available when the above lead times are applied.

Limited to 2 hoists per order.

Terms and Conditions of Sale

All sales are subject to the R&M Materials Handling, Inc. Standard Terms and Conditions of Sale (Revision 070810), a copy of which is available at www.rmhoist.com or upon request from your R&M Materials Handling, Inc. customer service/sales representatives and the terms of which are incorporated as if fully rewritten herein.

(Note 1) See SX Standard Hoist Features in the Spacemaster® SX price book for a list of standard hoist features.

(Note 2) See the following RX Program Hoist pages for voltage exceptions.



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.
Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



RX PROGRAM

Page 1
January 2, 2012

Suspension types - RX Hoist

Hoist Model	ASME Duty Class	Lift	Lift Speed (fpm)	Hoist Motor (hp)	Reeving	Low HR (L0)	Normal HR (N0)	Double Girder (D0)	D.G. Gauge (in)
-------------	-----------------	------	------------------	------------------	---------	-------------	----------------	--------------------	-----------------

1 Ton Capacity - Single Reeved

SX20210010P15FA	H4	39'-4"	40/6.6	3 / 0.4	2 P.S.	Yes	Yes	No	NA
SX20210010P15FC	H4	62'-4"	40/6.6	3 / 0.4	2 P.S.	Yes	Yes	No	NA
SX20210010R15FA	H4	39'-4"	20/3.3	1.5 / 0.4	2 P.S.	Yes ⁽³⁾	Yes ⁽³⁾	No	NA
SX20210010R15FC	H4	62'-4"	20/3.3	1.5 / 0.4	2 P.S.	Yes ⁽³⁾	Yes ⁽³⁾	No	NA
SX30210010P26FA	H4+	39'-4"	40/6.6	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26FC	H4+	62'-4"	40/6.6	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26GA	H4+	39'-4"	50/7.8	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA
SX30210010P26GC	H4+	62'-4"	50/7.8	4.7 / 0.7	2 P.S.	Yes	Yes	No	NA

1 1/2 Ton Capacity - Single Reeved

SX30210016P25FA	H4	39'-4"	40/6.6	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25FC	H4	62'-4"	40/6.6	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25GA	H4	39'-4"	50/7.8	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX30210016P25GC	H4	62'-4"	50/7.8	5.8 / 0.9	2 P.S.	Yes	Yes	No	NA
SX20410016P16FA	H4+	19'-8"	20/3.3	2.4 / 0.33	4 P.S.	Yes	Yes	No	NA
SX20410016P16FC	H4+	31'-2"	20/3.3	2.4 / 0.33	4 P.S.	Yes	Yes	No	NA

2 Ton Capacity - Single Reeved

SX20410020P15FA	H4	19'-8"	20/3.3	3 / 0.4	4 P.S.	Yes	Yes	No	NA
SX20410020P15FC	H4	31'-2"	20/3.3	3 / 0.4	4 P.S.	Yes	Yes	No	NA
SX40210020P36FB	H4+	39'-4"	40/6.6	5.8 / 0.9	2 P.S.	Yes	Yes	Yes	55.12
SX40210020P36FC	H4+	59'-0"	40/6.6	5.8 / 0.9	2 P.S.	Yes	Yes	Yes	55.12

For pricing, go to the SPACEMASTER® SX Hoist pages, and Hoist Speed Options pages.

(Note 3) 230v or 460v - 60Hz only

(Note 4) 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



RX PROGRAM

Page 2
January 2, 2012

Suspension types - RX Hoist

Hoist Model	ASME Duty Class	Lift	Lift Speed (fpm)	Hoist Motor (hp)	Reeving	Low HR (L0)	Normal HR (N0)	Double Girder (D0)	D.G. Gauge (in)
-------------	-----------------	------	------------------	------------------	---------	-------------	----------------	--------------------	-----------------

2 1/2 Ton Capacity - Single Reeved

SX30410025P26FA	H4+	19'-8"	20/3.3	4.7 / 0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26FC	H4+	31'-2"	20/3.3	4.7 / 0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26GA	H4+	19'-8"	25/3.9	4.7 / 0.7	4 P.S.	Yes	Yes	No	NA
SX30410025P26GC	H4+	31'-2"	25/3.9	4.7 / 0.7	4 P.S.	Yes	Yes	No	NA
SX40210025P35FB	H4	39'-4"	40/6.6	7.2 / 1.2	2 P.S.	Yes	Yes	Yes	55.12
SX40210025P35FC	H4	59'-0"	40/6.6	7.2 / 1.2	2 P.S.	Yes	Yes	Yes	55.12

3 Ton Capacity - Single Reeved

SX30410032P25FA	H4	19'-8"	20/3.3	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25FC	H4	31'-2"	20/3.3	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25GA	H4	19'-8"	25/3.9	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA
SX30410032P25GC	H4	31'-2"	25/3.9	5.8 / 0.9	4 P.S.	Yes	Yes	No	NA

5 Ton Capacity - Single Reeved

SX40410050P35FB	H4	19'-8"	20/3.3	7.2 / 1.2	4 P.S.	Yes	Yes	Yes	55.12
SX40410050P35FC	H4	29'-6"	20/3.3	7.2 / 1.2	4 P.S.	Yes	Yes	Yes	55.12
SX40410050P35FD	H4	39'-4"	20/3.3	7.2 / 1.2	4 P.S.	Yes	No	No	NA
SX50210050P55FD	H4	59'-0"	40/6.6	14.8 / 2.1	2 P.S.	Yes	Yes	Yes	55.12
SX50210050P55FE	H4	78'-8"	40/6.6	14.8 / 2.1	2 P.S.	Yes	No	Yes	55.12
SX50210050P65HD	H4	59'-0"	60/9.8	24.1 / 4	2 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50210050P65HE	H4	78'-8"	60/9.8	24.1 / 4	2 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12

For pricing, go to the SPACEMASTER® SX Hoist pages, and Hoist Speed Options pages.

(Note 3) 230v or 460v - 60Hz only

(Note 4) 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.
Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



RX PROGRAM

Page 3
January 2, 2012

						Suspension types - RX Hoist			
Hoist Model	ASME Duty Class	Lift	Lift Speed (fpm)	Hoist Motor (hp)	Reeving	Low HR (L0)	Normal HR (N0)	Double Girder (D0)	D.G. Gauge (in)
7 1/2 Ton Capacity - Single Reeved									
SX50410080P56FD	H4+	29'-6"	20/3.3	12 / 1.9	4 P.S.	Yes	Yes	Yes	55.12
SX50410080P56FE	H4+	39'-4"	20/3.3	12 / 1.9	4 P.S.	Yes	No	Yes	55.12
SX50410080P66HD	H4+	29'-6"	30/4.9	19 / 3	4 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50410080P66HE	H4+	39'-4"	30/4.9	19 / 3	4 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12
10 Ton Capacity - Single Reeved									
SX50410100P55FD	H4	29'-6"	20/3.3	14.8 / 2.1	4 P.S.	Yes	Yes	Yes	55.12
SX50410100P55FE	H4	39'-4"	20/3.3	14.8 / 2.1	4 P.S.	Yes	No	Yes	55.12
SX50410100P65HD	H4	29'-6"	30/4.9	24.1 / 4	4 P.S.	Yes ⁽⁴⁾	Yes ⁽⁴⁾	Yes ⁽⁴⁾	55.12
SX50410100P65HE	H4	39'-4"	30/4.9	24.1 / 4	4 P.S.	Yes ⁽⁴⁾	No	Yes ⁽⁴⁾	55.12
15 Ton Capacity - Single Reeved									
SX50610150P55FF	H4	32'-9"	13/2	14.8 / 2.1	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50610150P65HF	H4	32'-9"	20/3.3	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
15 Ton Capacity - Single Reeved									
SX50810160P55FF	H4	26'-2"	10/1.6	14.8 / 2.1	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50810160P65HF	H4	26'-2"	16/2.4	24.1 / 4	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74

For pricing, go to the SPACEMASTER® SX Hoist pages, and Hoist Speed Options pages.

(Note 3) 230v or 460v - 60Hz only

(Note 4) 460v or 575v - 60Hz only



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.
Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



RX PROGRAM

Page 4
January 2, 2012

						Suspension types - RX Hoist			
Hoist Model	ASME Duty Class	Lift	Lift Speed (fpm)	Hoist Motor (hp)	Reeving	Low HR (L0)	Normal HR (N0)	Double Girder (D0)	D.G. Gauge (in)
20 Ton Capacity - Single Reeved									
SX50810200P54FF	H3	26'-2"	10/1.6	14.8 / 2.1	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX50810200P64HF	H3	26'-2"	16/2.4	24.1 / 4	8 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610200P66EE	H4+	29'-6"	10/1.6	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610200P66FE	H4+	29'-6"	13/2	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610200P66EF	H4+	39'-4"	10/1.6	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610200P66FF	H4+	39'-4"	13/2	19 / 3	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
25 Ton Capacity - Single Reeved									
SX60610250P65EE	H4	29'-6"	10/1.6	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610250P65FE	H4	29'-6"	13/2	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74 ⁽⁵⁾
SX60610250P65EF	H4	39'-4"	10/1.6	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74
SX60610250P65FF	H4	39'-4"	13/2	24.1 / 4	6 P.S.	NA	No	Yes ⁽⁴⁾	78.74

For pricing, go to the SPACEMASTER® SX Hoist pages, and Hoist Speed Options pages.

(Note 3) 230v or 460v - 60Hz only

(Note 4) 460v or 575v - 60Hz only

(Note 5) 66.93" D.G. Gauge option - minimum 4 week lead time



R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502

www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.

Phone: 937-328-5100 Fax: 937-325-5319

Currency: USD
Units: US
Frequency: 60 Hz



Page 5
January 2, 2012

Hoist Options - RX Program

Control Transformer and Mainline Contactor (EL05)

Optional on Spacemaster® SX2 - SX6 Low and Normal headroom hoists only.

Pushbutton Pendant

Optional on Spacemaster® SX2 - SX6.

Patented Track Trolley Wheel (TR26)

Normal headroom hoist only.

Hook operated limit switch (manual reset) (HS22)

Optional on Spacemaster® SX2 - SX6. (This limit switch is in addition to the rotary limit switch.)
Addition of this limit switch increases headroom about 3 1/2" - 11" from standard depending on the hoist model. If headroom is critical, consult R&M for the actual headroom dimension.

HoistMonitor® (HS11), HoistMonitor® Select (HS12)

Optional on Spacemaster® SX2 - SX4 and SX5 with P5 motor
Optional on Spacemaster® SX6 with P6 and SX6 that do not include a control transformer and mainline contactor (EL05).
HoistMonitor® will be located in hoist electrical panel.

For pricing, go to the SPACEMASTER® SX hoist options pages.

R&M Materials Handling, Inc.
4501 Gateway Blvd.
Springfield, OH 45502



www.rmhoist.com

List prices FOB factory, Springfield, Ohio,
subject to change without notice.
Phone: 937-328-5100 Fax: 937-325-5319