R&M MATERIALS HANDLING INC.

Request for Quote

LoadMate® Electric Chain Hoists

FAX TO: 937-525-5130

Company: _____ Name: _____

Title: _____ E-mail: _____

Phone: _____ Fax: _____

1. Capacity: _____

2. Lift: _____

3. Suspension: ☐ Top Hook ☐ Lugmount ☐ Push Trolley
   ☐ Motorized Trolley ☐ Hand-geared Trolley

4. Hoist speed: _____

5. Hoist speed control: ☐ Single-speed ☐ Two-speed ☐ Variable-speed

6. Trolley speed control: ☐ Two-speed (Standard 2-speed is 80/20 fpm) ☐ Variable speed (Standard variable speed is 65/16 fpm)

7. Voltage: ☐ 460-3-60Hz ☐ 230-3-60Hz ☐ 208-3-60Hz ☐ 575-3-60Hz
   ☐ 115-1-60Hz ☐ Other: _____

8. Pendant to suit the lift? ☐ No ☐ Yes (Standard is 2.5 ft less than the amount of lift)

9. Location of use: ☐ Indoor ☐ Outdoor If outdoor, is it covered? _____

10. Duty cycle (ASME/FEM): ☐ H3/1Am ☐ H4/2m

11. Beam flange width: _____

12. Beam type: ☐ Straight track ☐ Curved track
    Radius _____ Switches? ☐ Yes ☐ No

13. Any special requirements? ☐ No ☐ Yes – Please call us at 800-955-9967!