



Request for Quote
Spacemaster® SX Wire Rope Hoists

FAX TO: 937-525-5130

Company: _____ Name: _____

Title: _____ E-mail: _____

Phone: _____ Fax: _____

1. Capacity: _____

2. Lift: _____

3. Suspension: Lugmount Footmount Push trolley
 Normal headroom Low headroom Double girder

4. Hoist speed: _____

5. Hoist control: Two-speed Variable speed (Open loop **OR** Closed loop)

6. Trolley speed: _____

7. Trolley control: Two-speed Variable speed (Standard is 65 fpm variable speed)

8. Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz 575-3-60Hz
 Other: _____

9. Reeving: Single-reeved Double-reeved

10. For a monorail or a crane? Monorail (For a monorail, we'll add a mainline contactor and control transformer.)
 Crane (For a crane, the mainline and control transformer are TYPICALLY in the bridge panel and not in the hoist panel.)

11. If for a monorail... Straight track Curved track
Radius _____ Switches? Yes No

12. Pendant required? No Yes Number of buttons? _____
Single speed? _____ 2-speed? _____

13. Location of use: Indoor Outdoor – Please call us at 800-955-9967!

14. Hoist duty cycle (ASME/FEM): H3/1Am H4/2m H4+/3m

15. Trolley duty cycle (CMAA/FEM): Class C/2m Class D/3m

16. Beam type / trolley rail size: _____

17. Beam flange width: _____

18. Any special requirements? No Yes – Please call us at 800-955-9967!