



# Request for Quote

## LoadMate® Electric Chain Hoists

**FAX: 937-525-5130**  
**EMAIL: See our contact list at**  
**<http://www.rmhoist.com/contact.htm>**

Company: \_\_\_\_\_ Name: \_\_\_\_\_

Phone: \_\_\_\_\_ E-mail: \_\_\_\_\_

### GENERAL

Capacity: \_\_\_\_\_

Lift: \_\_\_\_\_

- Suspension:  Top hook       Lugmount       Push trolley
- Motorized trolley       Hand-gearred trolley       Low headroom trolley
- Voltage:  460-3-60Hz       230-3-60Hz       208-3-60Hz
- 575-3-60Hz       115-1-60Hz       Other: \_\_\_\_\_

### HOIST AND TROLLEY

Hoist speed: \_\_\_\_\_

- Hoist control:  Single-speed       Two-speed       Variable-speed

Trolley speed: \_\_\_\_\_

- Trolley speed control:  Two-speed       Variable speed

Beam flange width: \_\_\_\_\_

Beam type:  Straight track       Curved track:      Radius: \_\_\_\_\_

Pendant required?  No       Yes      Length: \_\_\_\_\_

Power cord required?  No       Yes      Length: \_\_\_\_\_

Flat cord       Round cord

### ENVIRONMENT AND DUTY CYCLE

Location of use:  Indoor       Outdoor       Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): \_\_\_\_\_

Hoist duty cycle (ASME/FEM):  H3/1Am       H4/2m

QUOTE REQUIRED BY: \_\_\_\_\_

NOTES: