



# Request for Quote

## Stagemaker® Concert Hoists

**FAX: 937-525-5130**  
**EMAIL: See our contact list at**  
**<http://www.rmhoist.com/contact.htm>**

Company: \_\_\_\_\_

Name: \_\_\_\_\_

Phone: \_\_\_\_\_

E-mail: \_\_\_\_\_

### GENERAL

Capacity: \_\_\_\_\_

Quantity: \_\_\_\_\_

Lift: \_\_\_\_\_

Speed: \_\_\_\_\_

Voltage:  208-3-60Hz  230-3-60Hz  460-3-60Hz  400-3-50Hz  115-1-60Hz

Application Type:  Mobile (ex: concerts)  Fixed (ex: theaters)

Suspension:  Inverted (Chain up)  Normal (Chain down)

Configuration:  A (Direct control)  B (Low voltage - 3 phase power, 115 V control)

C (Programmable)  D (Enhanced safety)

E (VFD without controls)  S (115V single phase)

### ACCESSORIES

Pigtail arrangement:

- |  |               |                                       |  |
|--|---------------|---------------------------------------|--|
| <input type="checkbox"/> Power           | Length: _____ | <input type="checkbox"/> No connector | <input type="checkbox"/> Twist-lock connector                  |
| <input type="checkbox"/> Control         | Length: _____ | <input type="checkbox"/> No connector | <input type="checkbox"/> Twist-lock connector                  |
| <input type="checkbox"/> Power + Control | Length: _____ | Connector type:                       | <input type="checkbox"/> 7 Pin <input type="checkbox"/> 14 Pin |
| <input type="checkbox"/> None            |               |                                       |  |

Pinout requirement (Specify if selecting a 7 pin connector): \_\_\_\_\_  
(For R&M standard pinouts, please see the Stagemaker Technical Guide)

Pickle required:  No  Yes Length: \_\_\_\_\_  No connector  Twist-lock connector

### CONTROLLERS

For configuration B:  4 channel  8 channel  12 channel  
(Must be used with twist-lock, 7 pin, or 14 pin connectors)

For configuration S:  4 channel  8 channel  
(Must be used with twist-lock or 7 pin connectors)

QUOTE REQUIRED BY: \_\_\_\_\_

NOTES: