



- Motion Labs 4 channel modular motor control and power distribution system, 208 input (G, X, Y, Z) 3 Phase 5 Wire (Neutral Not Used)
- Dual Twist output rated for up to 4 1HP 3 Phase Electric Chain Hoists.
- Phase Reverse option to correct out of phase input.
- Contactor Enable button for local pendant control.
- Handheld Remote utilizes momentary switch for GO function and maintained switch for KILL function.
- KILL function disengages power to the motors.
- Unit built into 7 space 1 Iid NEMA 1 Steel Liner.
- Unit is ETL Listed in Canada and the United States and conforms to UL Standards 1640 for Portable Power Distribution and UL 508A for Industrial Controls as well as Canadian CSA Standard C22.2 No. 14
- Qualified Personnel Only

**Type 1 Enclosure**  
**Indoor Use Only**  
 Input Voltage: 208VAC, 3PH, 60Hz  
 Wiring Config: 4 CH @ 1HP  
 Max Ampracity: 20 Amps  
 Part No.: 1200-4-C-K-0703  
 Serial No.: XXXX

208 VAC  
 3PH 60 Hz  
 10 AMP/SP MAX.  
 PINOUT: 0900-01  
 L16-20  
 X = L1  
 Y = L2  
 Z = L3  
 Green = Ground  
 L14-20  
 X = Common  
 Y = Down  
 W = Up  
 G = Not Used



**motion laboratories**  
 520 Furnace Dock Road Cortlandt Manor, NY 10567  
 800-227-6784

Copyright © 2008, Motion Laboratories, Inc. All Rights Reserved. THIS DOCUMENT IS THE EXCLUSIVE CONFIDENTIAL PROPERTY OF MOTION LABORATORIES, INC. AND IT SHALL NOT BE REPRODUCED, COPIED, OR USED FOR ANY PURPOSE WHATSOEVER, UNLESS, AND STRICTLY TO THE EXTENT, SUCH IS EXPRESSLY AUTHORIZED BY MOTION LABORATORIES, INC. IN WRITING.

<b>TITLE</b>		<b>DRAWN BY</b>		<b>DATE DRAWN</b>		<b>SIZE</b>		<b>DRAWING NUMBER</b>		<b>REV</b>	
Motor Control, 4 CH, Input 208V 3PH L21-30FI, DT L16-20 Pwr L14-20 Ctl, PO-3A-AI0900-01, 2X10A3P, 7-1, w/Handheld		-		-		<b>A</b>		<b>1200-4-C-K-0703</b>		-	
<b>MODEL FILENAME &amp; PATH</b>		<b>CHECKED BY</b>		<b>DATE CHECKED</b>		<b>SCALE</b>		<b>SHT</b>		<b>OF</b>	
-		-		-		---		1		1	