



- Motion Labs 4 channel modular motor control and power distribution system.
208 Input (G, X, Y, Z) 3 Phase 4 Wire
- Dual Twist output rated for up to 8 1HP 3 Phase Electric Chain Hoists.
- Phase Reverse option to correct out of phase input.
- Contactor Enable button for local pendant control.
- Handheld Remote utilizes momentary switch for GO function and maintained switch for KILL function.
- KILL function disengages power to the motors.
- Unit built into 11 space 1 lid NEMA 1 Steel Liner.
- Unit is ETL Listed in Canada and the United States and conforms to UL Standards 1640 for Portable Power Distribution and UL 508A for Industrial Controls as well as Canadian CSA Standard C22.2 No. 14
- Qualified Personnel Only

Type 1 Enclosure
Indoor Use Only
Input Voltage: 208VAC 3PH 60Hz
Wiring Config: 8 CH @ 1HP
Max Ampacity: 40 Amps
Part No.: 1200-8-C-M-0703
Serial No.: XXXX

208 VAC
3PH 60 Hz
10 AMPS MAX.
P/NO: 0900-01
L16-20
X = L1
Y = L2
Z = L3
Green = Ground
L14-20
X = Common
Y = Down
W = Up
G = Not Used



motion laboratories
520 Furnace Dock Road Cortlandt Manor, NY 10567
800-227-6784

Copyright © 2008, Motion Laboratories, Inc. All Rights Reserved. THIS DOCUMENT IS THE EXCLUSIVE CONFIDENTIAL PROPERTY OF MOTION LABORATORIES, INC. AND IT SHALL NOT BE REPRODUCED, COPIED, OR USED FOR ANY PURPOSE WHATSOEVER, UNLESS, AND STRICTLY TO THE EXTENT, SUCH IS EXPRESSLY AUTHORIZED BY MOTION LABORATORIES, INC. IN WRITING.

TITLE		SIZE		DRAWING NUMBER		REV	
Motor Control 8 CH, Input 50A 480V 3PH, DT L16-20 Pwr L14-20 Ctl, PO-3A-A10900-01, 4X10A3P, 11-1, w/Handheld		A		1200-8-C-M-0703		-	
DRAWN BY	DATE DRAWN	CHECKED BY	DATE CHECKED	MODEL FILENAME & PATH	SCALE	SHT	OF
-	-	-	-	-	---	1	1